Supplier - SMART OIL
Smart Base 1120

Sulfurized Fatty Oil

Typical Properties

Appearance	Dark Brown Liquid
Specific Gravity@25℃	0.950 - 1.000
Viscosity@40°C, cSt	450 - 950
Sulfur Content (Active), %wt	10 - 12 (0)
Acid Value, mgKOH/g	≤ 8
Flash Point C.O.C., °C	> 170
Copper Corrosion+	1B
P_B/P_D , $kg++$	88 / 250
Std Packaging (NW / GW, Kg)	217.0 / 200.0

Product Description

SMART BASE 1120 is a premium inactive sulfurized lard oil additive; suitable for machining different kinds of ferrous and non-ferrous metals.

SMART BASE 1120 will not cause corrosion of brass and bronze under normal machining condition; so suitable for severe operations on non-ferrous metals.

SMART BASE 1120 possesses superior EP and lubricity properties; suitable for waylube, cutting oil and rolling oil formulations.

SMART BASE 1120 can be blended with tackifier such as SmartTac H and Group I ISO 68 and ISO 220 grade base oil to prepare for the heavy-medium way lubricant of the CINCINNATI MILACRON P-47 and heavy way lubricant of the CINCINNATI MILACRON P-47 respectively.

Recommended treat rate is: **SMART BASE 1120** 5%, **SmartTac H** 0.5%, Base Oil 94.5%.

<u>Applications</u>	<u>Suggested Treat Rates, %wt</u>
Threading	10 - 15
Tapping	10 - 20
Tapping	10 - 20
Rolling Oil	3 - 10

Print date: 04-02-25