Supplier - SMART OIL
Smart Base 2510

Sulfurized Fatty Oil

## **Typical Properties**

Appearance	Clear Amber Liquid
Specific Gravity@25°C	0.900 - 1.000
Viscosity@40°C, cSt	45 - 90
Sulfur Content (Active), %wt	8.5 - 10.5 (<4)
Acid Value, mgKOH/g	≤ 9
Flash Point C.O.C., °C	> 145
Copper Corrosion+	1B
$P_B/P_D$ , kg++	76 / 250
Std Packaging (NW / GW, Kg)	212.0 / 195.0

## **Product Description**

**SMART BASE 2510** is an inactive EP additive with clear amber colour, low odor and sulfurized fatty oil, possessing good lubricity and anti-wear properties. It is designed for use in neat oil and soluble oil formulations, applying for both ferrous and non-ferrous metals.

**SMART BASE 2510** possesses low viscosity and is easy to be blended with other additives and mineral oils. It exhibits superior EP property when compared to conventional equivalent amounts of sulfur-containing additives.

SMART BASE 2510 will not corrode yellow metals, so it can be used to machine brass and bronzes.

**SMART BASE 2510** is highly stable and compatible with other additives and different groups of base oils, which make it easy for blenders to use for blending different types of machining oils.

<u>Applications</u>	Suggested Treat Rates, %wt
Threading	3 - 15
Threading	3 - 15
Cold Head (Cut Side Only)	5 - 20
Automatic Screw Machines (Cut Side	5 - 15
Only)	
Turning	2 - 8

Print date: 04-02-25