

Supplier - FUNCTIONAL
V-158

Viscosity Index Improver

Typical Properties

Specific Gravity	0.850
Density,lbs/gal	7.1
Flash Point,°C(°F)	175 (350)
Kinematic Viscosity@100°C,cSt	1250
Color	Yellow (1 - 2ASTM)
Thickening Efficiency@100°C(14.5% in ISO 32 Paraffinic Base Oil)	12.5 - 15.5
Shear Stability(10-hr L-38 Test, MIL-L-46152)	28%Thickening Loss
Shear Stability Index(PSSI)ASTM D 6278	45%Thickening Loss

Product Description

FUNCTIONAL V-158 is a viscosity index (V.I.) improver that may be used in preparing multi-grade engine oils as well as industrial fluids and lubricants. It may also be used without dilution as a supplemental crankcase additive for the automotive aftermarket.

COMPOSITION:

The active thickener in **FUNCTIONAL V-158** is a copolymer of ethylene and propylene that has been used as a V.I. improver by major oil companies. The diluent in **FUNCTIONAL V-158** is a light paraffinic mineral oil.

HANDLING:

Due to the viscosity of **FUNCTIONAL V-158**, elevated temperature (up to approximately 90°C or 200°F) can facilitate handling. Safe handling precautions are the same as those to be taken with the base oil; see the current Material Safety Data Sheet.

Applications

Industrial Lubricants and Greases

Suggested Treat Rates, %wt

5 - 20

Print date: 04-02-25

Disclaimer: Information provided by this website and product page including specifications, applications and formulations are based on tests and data supplied by Smart Oil companies, manufacturers or any of our collaborated companies or suppliers, which are believed to be correct and reliable at the time of writing and data update. However, Smart Oil companies, manufacturers or any of our collaborated companies or suppliers make no warranty or responsibility, express or implied, of any kind regarding products, performance, formulations or applications, as operation conditions and application environments are beyond our control, or products will be modified by action of manufacturers or due to change in market environments. Users are herewith expressly requested to conduct test to determine the suitability of our products or product information before use. Furthermore, we regret that we cannot be responsible for informing customers any changes in specifications, formulations, or other technical contents on this website and product page. Also, We hereby state that all product trademarks other than Smart Oil, including trademarks from our , suppliers are the trademarks belong to the respective companies, or from their sources.