

Supplier - FUNCTIONAL

V-4004A*Multifunctional Liquid Polymer for Greases*Typical Properties

Specific Gravity(ASTM D1298)	0.880
Density (TM-04),lbs/gal	7.30
Flash Point(ASTM D92),°C(°F)	130 (270)
Kinematic Viscosity@100°C(ASTM D445),cSt	500 - 800
Color(ASTM D1500)	< 4 (Yellow-Orange)

Product Description

FUNCTIONAL V-4004A is a multifunctional polymer specifically designed for use in greases to improve water resistance and mechanical stability. Its liquid form allows quick incorporation into grease without long dissolving process. It can be added to grease in the final – finishing stage. **FUNCTIONAL V-4004A** also increases the tackiness of the grease and reduces the soap content (higher yields).

COMPOSITION:

FUNCTIONAL V-4004A is a hydrocarbon polymer diluted in light-colored naphthenic oil that does not require hazard labeling. It is chemically different from motor oil V.I. improver polymers in its monomer content.

HANDLING:

Due to the high viscosity of **FUNCTIONAL V-4004A**, elevated temperature about 150°F (65°C) can facilitate handling, but temperatures over 200°F (95°C) should be avoided. Safe handling precautions are the same as those to be taken with the base oil; see the current MSDS. The tackiness of the resulting lubricant can be lessened by shearing, so mechanical shearing during blending and handling should be minimized.

Applications

Typical Application

Suggested Treat Rates, %wt

1.0 - 5.0

Print date: 04-02-25

Disclaimer: Information provided by this website and product page including specifications, applications and formulations are based on tests and data supplied by Smart Oil companies, manufacturers or any of our collaborated companies or suppliers, which are believed to be correct and reliable at the time of writing and data update. However, Smart Oil companies, manufacturers or any of our collaborated companies or suppliers make no warranty or responsibility, express or implied, of any kind regarding products, performance, formulations or applications, as operation conditions and application environments are beyond our control, or products will be modified by action of manufacturers or due to change in market environments. Users are herewith expressly requested to conduct test to determine the suitability of our products or product information before use. Furthermore, we regret that we cannot be responsible for informing customers any changes in specifications, formulations, or other technical contents on this website and product page. Also, We hereby state that all product trademarks other than Smart Oil, including trademarks from our , suppliers are the trademarks belong to the respective companies, or from their sources.