

Supplier - FUNCTIONAL
V-162*Antimisting Additive*Typical Properties

Specific Gravity	0.860
Density,lbs/gal	7.16
Flash Point,°C(°F)	170 (300)
Kinematic Viscosity@40°C,cSt	600 - 900
Color(ASTM D1500)	< 4

Product Description

FUNCTIONAL V-162 is an additive for reducing stray misting. It can be formulated into an oil-based cutting oil to reduce the oil mist during use. Unlike some other anti-misting additives, **FUNCTIONAL V-162** does not make the lubricant tacky. Where tackiness is desired, **FUNCTIONAL V-189** is recommended instead. **FUNCTIONAL V-162** may also be used as a tankside additive to compensate for the loss due to shearing in use, or to provide extra anti-misting protection for specific problem equipment.

COMPOSITION

The active ingredient in **FUNCTIONAL V-162** is the particular grade of polyisobutylene selected by the research program at Ford Motor Company and Wayne State University. The diluent oil in **FUNCTIONAL V-162** is light paraffinic oil that permits easy blending. The ingredients of **FUNCTIONAL V-162** are non-hazardous.

HANDLING

Due to the low viscosity of **FUNCTIONAL V-162**, elevated temperature is not necessary. Safe handling precautions are the same as those to be taken with the base oil; see the current Material Safety Data Sheet.

Applications

General Application

Suggested Treat Rates, %wt

0.02 - 0.1

Print date: 04-02-25

Disclaimer: Information provided by this website and product page including specifications, applications and formulations are based on tests and data supplied by Smart Oil companies, manufacturers or any of our collaborated companies or suppliers, which are believed to be correct and reliable at the time of writing and data update. However, Smart Oil companies, manufacturers or any of our collaborated companies or suppliers make no warranty or responsibility, express or implied, of any kind regarding products, performance, formulations or applications, as operation conditions and application environments are beyond our control, or products will be modified by action of manufacturers or due to change in market environments. Users are herewith expressly requested to conduct test to determine the suitability of our products or product information before use. Furthermore, we regret that we cannot be responsible for informing customers any changes in specifications, formulations, or other technical contents on this website and product page. Also, We hereby state that all product trademarks other than Smart Oil, including trademarks from our , suppliers are the trademarks belong to the respective companies, or from their sources.