Supplier - FUNCTIONAL PD-610

Cold-flow Improver for Mineral Oil-based Lubricants

Typical Properties

Appearance Clear Viscous Liquid Color Pale Yellow to Amber Specific Gravity 0.900 Flash Point, $^{\circ}$ C \geq 150 Kinematic Viscosity@100 $^{\circ}$ C,cSt < 800

Product Description

FUNCTIONAL PD-610 is a wax-crystal modifier. Its primary use is in improving the cold flow properties of mineral oil-based lubricants at temperatures below their cloud points. It is effective under both rapid-cooling conditions and extended cold storage conditions. **FUNCTIONAL PD-610** is effective in hydraulic fluids, chain saw oils, pneumatic-tool lubricants and other lubricants made from solvent extracted neutral base stocks as well as hydro-cracked base stocks.

Composition:

The active additive in **FUNCTIONAL PD-610** is a proprietary polymer. The diluent oil in **FUNCTIONAL PD-610** is light paraffinic oil.

Handling:

Any convenient technique may be used for blending. Safe handling precautions are the same as those to be taken with vegetable oils; see the current Material Safety Data Sheet.

ApplicationsGeneral Application

Suggested Treat Rates, %wt 0.1 - 0.5

Print date: 04-02-25